Stabilit Suisse S.A. Via Lische 11/13 P.O. Box 702 - 6855 Stabio (CH) P. Iva CHE-101.684.884



DECLARATION OF PERFORMANCE No. 00705191128

Unique identification code of the product-type: 007
Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): Macrolux Multiwall 10X 32 mm - 3700
Intended uses: For internal and external roofs, walls and ceilings
Manufacturer: Stabilit Suisse SA Registered Office & Factory Via Lische 11/13 - P.O. Box 702 6855 - Stabio - Switzerland
System AVCP: System 3
Harmonised standard: EN 16153:2013+A1:2015
Notified body: NB 1168 (AFITI-LICOF)

Declared performances:

Essential characteristics	Performance
Visual appearance	Pass
Dimensional tolerances	Pass
External fire performance	F _{ROOF} (NPD)
Reaction to fire	B, s1, d0
Resistance to fire	NPD
Water vapour permeability	3,8 x 10-5 mg/m x h x Pa
Water/air permeability	Pass
Release of dangerous substances	NPD



Shatter properties (safe breakability) as: Small hard body impact resistance	Pass
Large soft body impact resistance (assembly)	NPD
Mechanical resistance (deformation behaviour)	NPD
Thermal transmittance	$U = 1.2 \text{ W/m}^2 \text{ K (Horizontal position)}$
	$U = 1.1 \text{ W/m}^2 \text{ K (Vertical position)}$
Light transmittance	$T_{\rm v} = 47\%$ (Clear)
Total solar energy transmittance	g = 51% (Clear)
	$T_e = 47\%$ (Clear)
	$T_e = 35\%$ (Opal)
Resistance to fixings	Method of fixing (see technical handbook)
	Metodo di fissaggio (vedi manuale tecnico)
Linear thermal expansion	65 x 10 ⁻⁶ K ⁻¹
Durability, as variation (after ageing) of the light transmission	Clear Δ_{A}
	Other colours $\Delta_{ m D}$
Durability, as variation (after ageing) of the yellowness index	Clear Δ_{A}
	Other colours $\Delta_{ m D}$
Durability, as variation (after ageing) of tensile strength	Ku 1
Durability, as variation (after ageing) on flexural modulus	Cu 1
Direct airborne sound insulation	NPD

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Matteo Borsani Product manager

At Stabio (Switzerland) on 10.11.2022

Stabilit Suisse S.A. Via Lische 11/13 P.O. Box 702 - 6855 Stabio (CH) P. Iva CHE-101.684.884



Stabilit Suisse SA
Via Liscre W13 - P.O. Box 702
6855 Stabio - Switzerland
Plya Cills 104-684,884